

## 92. Recommended spare parts: AP, APG

50/60 Hz

### Customer Information

Project title:	Customer name:
Reference number:	Customer number:
Customer contact:	Customer phone number: ( )
	Fax number: ( )

### Pump information

### Quotation made by

<input type="radio"/>	<input type="radio"/>					
Type Prod. No.						
P.c.	Ø mm					
▽	T °C	IP	Insul. class:			
Model	Pol	Hz	V			
P <sub>1</sub> /P <sub>2</sub>	KW	I <sub>N</sub>	A	I <sub>start</sub>	A <sub>n</sub>	/min
Cos φ			Weight	kg		
Ex						
<input type="radio"/>	<input type="radio"/>					

GRUNDFOS   
CH-6105 Schachen

Company name:

Prepared by:

Phone number: ( )

Fax number: ( )

Date:

Quote number:

### Recommended spare parts

	Recommended service parts						Product number
	1 pump		2 to 3 pumps		4 to 7 pumps		
Kit - Spare - Bulk	2 years units per pump	5 years units per pump	2 years units per pump	5 years units per pump	2 years units per pump	5 years units per pump	Product number
Kit, Wear Part Kit	1	2	2	3	4	8	
Oil*	1	2	2	3	4	8	

\* See service instruction for amount and type.

Above recommendations are based on:

Agitators running in normal operation should be checked every 3000 operating hours or at least once a year.  
If the stirred liquid is very muddy or sandy, check the pump at shorter intervals.