



Tipo Type	Dimensioni - Dimensions														Bull. fiss. Bolt Size	Coefficienti di carico (N) Load ratings (N)		Cuscinetto Bearing	Supporto Housing	Peso Weight	
	d	a	p	e	i	s	j	k	g	f	z	t	B	n		Dinamico C Dynamic C	Statico C ₀ Static C ₀				
	mm/inch															mm/inch				kg	
UCFC201	12	100	78	55,1	10	12	5	7	20,5	62	28,3	32,5	31	12,7	M10			UC201		0,73	
UCFC201-8	½	315/16	35/64	211/64	25/64	15/32	13/64	9/32	13/16	2,4409	11/8	19/32	1,2205	0,500	3/8	12160	6318	UC201-8	FC204	0,72	
UCFC202	15	100	78	55,1	10	12	5	7	20,5	62	28,3	32,5	31	12,7	M10			UC202		0,72	
UCFC202-9	9/16	315/16	35/64	211/64	25/64	15/32	13/64	9/32	13/16	2,4409	11/8	19/32	1,2205	0,500	3/8	12160	6318	UC202-9	FC204	0,72	
UCFC202-10	5/8	315/16	35/64	211/64	25/64	15/32	13/64	9/32	13/16	2,4409	11/8	19/32	1,2205	0,500	3/8			UC202-10	FC204	0,72	
UCFC203	17	100	78	55,1	10	12	5	7	20,5	62	28,3	32,5	31	12,7	M10			UC203		0,71	
UCFC203-11	11/16	315/16	35/64	211/64	25/64	15/32	13/64	9/32	13/16	2,4409	11/8	19/32	1,2205	0,500	3/8	12160	6318	UC203-11	FC204	0,70	
UCFC204	20	100	78	55,1	10	12	5	7	20,5	62	28,3	32,5	31	12,7	M10			UC204		0,69	
UCFC204-12	¾	315/16	35/64	211/64	25/64	15/32	13/64	9/32	13/16	2,4409	11/8	19/32	1,2205	0,500	3/8	12160	6318	UC204-12	FC204	0,69	
UCFC205	25	115	90	63,6	10	12	6	7	21	70	29,8	34	34,1	14,3	M10			UC205		1,00	
UCFC205-13	13/16	417/32	335/64	2½	25/64	15/32	15/64	9/32	53/64	2,7559	111/64	111/32	1,3425	0,563	3/8	13300	7457	UC205-13	FC205	1,04	
UCFC205-14	7/8																	UC205-14	FC205	1,03	
UCFC205-15	15/16																	UC205-15	FC205	1,01	
UCFC205-16	1																	UC205-16	FC205	1,00	
UCFC206	30	125	100	70,7	10	12	8	8	23	80	32,2	36,5	38,1	15,9	M10			UC206		1,30	
UCFC206-17	11/16	459/64	315/16	225/32	25/64	15/32	5/16	5/16	29/32	3,1496	117/64	17/16	1,5000	0,626	3/8	18525	10735	UC206-17	FC206	1,31	
UCFC206-18	11/8																	UC206-18	FC206	1,32	
UCFC206-19	13/16																	UC206-19	FC206	1,30	
UCFC206-20	1½																	UC206-20	FC206	1,29	
UCFC207	35	135	110	77,8	11	14	8	9	26	90	36,4	41	42,9	17,5	M12			UC207		1,81	
UCFC207-20	1¼	55/16	421/64	31/16	7/16	35/64	5/16	23/64	11/32	3,5433	17/16	15/8	1,6890	0,689	7/16	24415	14630	UC207-20	FC207	1,87	
UCFC207-21	15/16																	UC207-21	FC207	1,84	
UCFC207-22	13/8																	UC207-22	FC207	1,81	
UCFC207-23	17/16																	UC207-23	FC207	1,78	
UCFC208	40	145	120	84,8	11	14	10	9	26	100	41,2	45,5	49,2	19	M12			UC208		2,14	
UCFC208-24	1½	545/64	423/32	311/32	7/16	35/64	25/64	23/84	11/32	3,9370	15/8	151/64	1,9370	0,748	7/16	27645	16910	UC208-24	FC208	2,18	
UCFC208-25	19/6																	UC208-25	FC208	2,15	
UCFC209	45	160	132	93,3	10	16	12	14	26	105	40,2	44,5	49,2	19	M14			UC209		2,68	
UCFC209-26	15/8	619/64	513/64	343/64	25/64	5/8	15/32	35/64	11/32	4,1339	137/64	1¾	1,9370	0,748	½	32395	20235	UC209-26	FC209	2,78	
UCFC209-27	111/64																	UC209-27	FC209	2,74	
UCFC209-28	1¾																	UC209-28	FC209	2,70	
UCFC210	50	165	138	97,6	10	16	12	14	28	110	42,6	47,5	51,6	19	M14			UC210		2,90	
UCFC210-29	113/16	6½	57/16	327/32	25/64	5/8	15/32	35/64	17/64	4,3307	11/16	17/8	2,0315	0,748	½	33345	22135	UC210-29	FC210	3,02	
UCFC210-30	17/8																	UC210-30	FC210	2,97	
UCFC210-31	115/16																	UC210-31	FC210	2,92	
UCFC210-32	2																	UC210-32	FC210	2,88	
UCFC211	55	185	150	106,1	13	19	12	15	31	125	46,4	51	55,6	22,2	M16			UC211		4,01	
UCFC211-32	2	79/32	529/32	43/16	33/64	¾	15/32	19/32	17/32	4,9213	153/64	21/64	2,1890	0,874	5/8	41230	27930	UC211-32	FC211	4,16	
UCFC211-33	21/16																	UC211-33	FC211	4,10	
UCFC211-34	21/8																	UC211-34	FC211	4,05	
UCFC211-35	23/16																	UC211-35	FC211	3,99	
UCFC212	60	195	160	113,1	17	19	12	15	36	135	56,7	61,5	65,1	25,4	M16			UC212		4,94	
UCFC212-36	2¼	711/16	619/64	429/64	43/64	¾	15/32	19/32	127/64	5,3150	215/64	227/64	2,5630	1,000	5/8	49780	34390	UC212-36	FC212	5,07	
UCFC212-37	25/16																	UC212-37	FC212	4,99	
UCFC212-38	23/8																	UC212-38	FC212	4,92	
UCFC212-39	27/16																	UC212-39	FC212	4,85	
UCFC213	65	205	170	120,2	16	19	14	15	36	145	55,7	60,5	65,1	25,4	M16			UC213		5,65	
UCFC213-40	2½	85/64	611/16	447/64	5/8	¾	35/64	19/32	127/64	5,5118	13/16	225/64	2,5630	1,000	5/8	54340	38095	UC213-40	FC213	5,74	
UCFC213-41	29/16																	UC213-41	FC213	5,65	
UCFC214	70	215	177	125,1	17	19	14	18	40	150	61,4	-	74,6	30,2	M16			UC214		6,95	
UCFC214-42	25/8	815/32	631/32	459/64	43/64	¾	35/64	23/32	137/64	5,9055	113/32	-	2,9370	1,189	5/8	59090	41895	UC214-42	FC214	7,16	
UCFC214-43	211/64																	UC214-43	FC214	7,06	
UCFC214-44	2¾																	UC214-44	FC214	6,96	
UCFC215	75	220	184	130,1	18	19	16	18	40	160	62,5	-	77,8	33,3	M16			UC215		7,56	
UCFC215-45	213/16	831/32	7¼	51/8	23/32	¾	5/8	23/32	137/64	6,2992	215/32	-	3,0630	1,311	5/8	64030	45885	UC215-45	FC215	7,81	
UCFC215-46	27/8																	UC215-46	FC215	7,70	
UCFC215-47	215/16																	UC215-47	FC215	7,59	
UCFC215-48	3																	UC215-48	FC215	7,47	
UCFC216	80	240	200	141,4	18	23	16	18	42	170	67,3	-	82,6	33,3	M20			UC216		9,15	
UCFC216-49	31/16	929/64	77/8	59/16	23/32	29/32	5/8	23/32	121/32	6,6929	221/32	-	3,2520	1,311	¾	69065	50350	UC216-49	FC216	9,28	
UCFC216-50	31/8																	UC216-50	FC216	9,20	
UCFC216-51	33/16																	UC216-51	FC216	9,07	
UCFC217	85	250	208	147,1	18	23	18	20	45	180	69,6	-	85,7	34,1	M20			UC217		10,81	
UCFC217-52	3¼	35/16	927/32	83/16	551/64	23/32	29/32	23/32	25/32	125/32	7,0866	2¾	-	3,3740	1,343	¾	79800	58805	UC217-52	FC217	11,03
UCFC217-53	35/16																	UC217-53	FC217	10,89	
UCFC217-55	37/16																	UC217-55	FC217	10,60	
UCFC218	90	265	220	155,5	22	23	18	20	50	190	78,3	-	96	39,7	M20			UC218		12,96	
UCFC218-56	3½	107/16	821/32	61/8	55/64	29/32	23/32	25/32	131/32	7,4803	33/32	-	3,7795	1,5630	¾	91295	67925	UC218-56	FC218	13,07	

Disponibile in acciaio inox Supporto: AISI 304 - Cuscinetto: AISI 440C o 420C - Available stainless steel Housing: AISI 304 - Bearing: AISI 440C or 420C
Disponibile su richiesta con cuscinetto SA (SAFC...) - Available under request with SA bearing (SAFC...)