

# Product data sheet

## Characteristics

### XZCPV0566L5

pre-wired connectors XZ - straight female - M8  
- 3 pins - cable PVC 5m



#### Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

#### Complementary

Electrical connection	Straight female connector M8, 3 pins
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	5 m
Cable outer diameter	4.6 mm
Cable composition	3 x 0.25 mm <sup>2</sup>
Wire insulation material	PVC
[Ue] rated operational voltage	60 V AC 75 V DC
[In] rated current	3 A
Contact resistance	5000 µOhm
Minimum insulating resistance	1 GΩ
Net weight	0.153 kg

#### Environment

IP degree of protection	IP65 IP67
Product certifications	CULus
Ambient air temperature for operation	-25...80 °C static
Ambient air temperature for storage	-25...80 °C

#### Packing Units

Package 1 Weight	0.158 kg
Package 1 Height	0.200 dm
Package 1 width	1.650 dm
Package 1 Length	2.000 dm

## Offer Sustainability

REACH Regulation	<input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <input checked="" type="checkbox"/> <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes


## Contractual warranty

Warranty	18 months
----------	-----------

---

Dimensions

---




L : Length of cable

---

Connections and Schemes

---

Connector



BU : Blue

BN : Brown

BK : Black