

## Technical data sheet Interconnection cable

Part no.: 50133387

KSS ET-M12-8A-RJ45-A-P7-050

### Contents

- Technical data
- Electrical connection



Figure can vary



## Technical data

### Basic data

Suitable for interface	Ethernet
------------------------	----------

### Electrical data

#### Performance data

### Connection

#### Connection 1

Type of connection	Connector
Thread size	M12
Type	Male
No. of pins	8 -pin
Encoding	X-coded
Design	Axial

#### Connection 2

Type of connection	RJ45
Type	Male
No. of pins	8 -pin
Design	Axial

#### Cable properties

Number of conductors	8 Piece(s)
Sheathing color	Black
Shielded	Yes
Silicone-free	Yes
Cable design	Interconnection cable
Cable length	5,000 mm
Sheathing material	PUR
Suitability for drag chains	Yes
Traverse rate	Max. 3.3 m/s with horiz. traverse path of 5m and and max. acceleration of 5m/s <sup>2</sup>

### Mechanical data

Width across flats	13 mm
--------------------	-------

### Environmental data

Ambient temperature, operation, flexible use	-40 ... 80 °C
--	---------------

### Certifications

Degree of protection	IP 67
----------------------	-------

### Classification

Customs tariff number	85444290
eCl@ss 8.0	27279218
eCl@ss 9.0	27060311
ETIM 5.0	EC001855
ETIM 6.0	EC001855

## Electrical connection

### Connection 1

Type of connection	Connector
Thread size	M12
Type	Male
No. of pins	8 -pin
Encoding	X-coded
Design	Axial

### Connection 2

Type of connection	RJ45
--------------------	------