




Cable connector V112S-G-BK5M-PUR-ABG

- Immunity to vibration, with mechanical latching
- Knurled nut suitable for tool assembly
- Suitable for drag chains and abrasion resistant
- Resistant to microbes and hydrolysis
- Halogen-free

Male cordset single-ended M12 A-coded, 12-pin, PUR cable black, shielded

Dimensions



Technical Data

General specifications

Connector 1		
Connection		Male connector
Construction type		M12
Style		straight
Locking		screw connection
Number of pins		12
Coding		A-coded
Connector 2		
Connection		cable end

Electrical specifications

Operating voltage	U_B	30 V
Operating current	I_B	1.5 A
Surge protection		category II

Conformity

Degree of protection		EN 60529
Plug connection		connector M12 x 1 : IEC 61076-2-101

Release date: 2020-08-12 Date of issue: 2020-08-12 Filename: 70115002_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com



 **PEPPERL+FUCHS**

Technical Data

Flammability		IEC 60332-1-2 , UL 1581
Chemical resistance		DIN VDE 0472 T.803, test type B
Microbial resistance		DIN VDE 0282-10 / EN 50396
Ambient conditions		
Ambient temperature		
Plug connector		-25 ... 85 °C (-13 ... 185 °F)
Cable, fixed		-30 ... 80 °C (-22 ... 176 °F)
Cable, flexing		-5 ... 80 °C (23 ... 176 °F)
Pollution degree		3
Mechanical specifications		
Plug connector		
Tightening torque		0.6 Nm
Tool installation		straight knurling
Mating cycles		min. 100
Shielding		shield connected to screw connection
Degree of protection		IP65/IP67
Cable		according to IEC/EN 60228 (DIN VDE 0295) class 5
Sheath diameter		8.5 mm
Bending radius		> 10 x cable diameter, moving > 5 x cable diameter, fixed
Sheath color		black (similar to RAL 9005)
Number of cores		12
Core cross-section		0.14 mm ²
Cores color		Core 1: brown Core 2: blue Core 3: white Core 4: green Core 5: pink Core 6: yellow Core 7: black Core 8: grey Core 9: red Core 10: violet Core 11: grey/pink Core 12: red/blue
Core construction		18 x 0.1 mm Ø twisted pairs
Shield		tinned copper braiding, 85 % coverage
Length	L	5 m
Cable code		LSPYwC11Y
Drag chain suitability		
Drag chain cycles		min. 2000000
Motion velocity		max. 3 m/s
Traverse distance		10 m
Acceleration		max. 10 m/s ²
Material		
Plug connector		
Knurled screw connection		Zinc die-casting, nickel-plated
Body		TPU, green
Seal		NBR
Contact surface		Ni/Au
Flammability		V-0
Cable		
Sheathing		PUR
Core insulation		PP
Flammability		VW-1

Release date: 2020-08-12 Date of issue: 2020-08-12 Filename: 70115002_eng.pdf

Connection



Accessories

	MH V1-SCREWDRIVER	torque screwdriver (0.6 Nm)
	MH V1-BIT M12	plug-in cap M12
	V1/V3-LABELHOLDER	Label holder
	V1/V3-LABEL	Label plate
	MH V1-Holder	Modular universal holder for M12 connectors
	V1-MARKING-RING-BLUE	Marking ring for M12 connectors
	V1-MARKING-RING-GREEN	Marking ring for M12 connectors
	V1-MARKING-RING-ORANGE	Marking ring for M12 connectors
	V1-MARKING-RING-RED	Marking ring for M12 connectors
	V1-MARKING-RING-WHITE	Marking ring for M12 connectors
	V1-MARKING-RING-YELLOW	Marking ring for M12 connectors