




## Female connector V19-W-BK0,3M-PUR-U

- Degree of protection IP67 / IP68 / IP69
- Free from substances that impair paint wetting
- Resistant to microbes and hydrolysis
- cURus approval
- UV resistant
- Halogen-free
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching

Female cordset single-ended M12 angled A-coded, 8-pin, PUR cable black, UL approved, drag chain suitable, torsion resistant



### Dimensions



### Technical Data

#### General specifications

|                   |  |                  |
|-------------------|--|------------------|
| Connector 1       |  |                  |
| Connection        |  | socket           |
| Construction type |  | M12              |
| Style             |  | right angle      |
| Locking           |  | screw connection |
| Number of pins    |  | 8                |
| Coding            |  | A-coded          |
| Connector 2       |  |                  |
| Connection        |  | cable end        |
| UL File Number    |  | E231213          |

#### Electrical specifications

|                   |       |                 |
|-------------------|-------|-----------------|
| Operating voltage | $U_B$ | max. 30 V AC/DC |
| Operating current | $I_B$ | max. 2 A        |

#### Conformity


|                      |          |
|----------------------|----------|
| Degree of protection | EN 60529 |
|----------------------|----------|

## Technical Data

|                                   |   |                                                                                                                                  |
|-----------------------------------|---|----------------------------------------------------------------------------------------------------------------------------------|
| Plug connection                   |   | connector M12 x 1 : IEC 61076-2-101                                                                                              |
| Flammability                      |   | UL 1581; DIN EN 60332-2-2                                                                                                        |
| Halogen-free                      |   | IEC 60754-1                                                                                                                      |
| <b>Approvals and certificates</b> |   |                                                                                                                                  |
| UL approval                       |   | AWM STYLE 20549 AWM I/II A/B 80°C 300V FT2 (cable)                                                                               |
| <b>Ambient conditions</b>         |   |                                                                                                                                  |
| Ambient temperature               |   |                                                                                                                                  |
| Plug connector                    |   | -40 ... 90 °C (-40 ... 194 °F)                                                                                                   |
| Cable, fixed                      |   | -40 ... 80 °C (-40 ... 176 °F)                                                                                                   |
| Cable, flexing                    |   | -20 ... 80 °C (-4 ... 176 °F)                                                                                                    |
| Pollution degree                  |   | 3                                                                                                                                |
| <b>Mechanical specifications</b>  |   |                                                                                                                                  |
| Plug connector                    |   |                                                                                                                                  |
| Tightening torque                 |   | 0.6 Nm                                                                                                                           |
| Loosening protection              |   | available                                                                                                                        |
| Tool installation                 |   | straight knurling                                                                                                                |
| Mating cycles                     |   | min. 100                                                                                                                         |
| Degree of protection              |   | IP67 / IP68 / IP69                                                                                                               |
| Cable                             |   | according to IEC/EN 60228 (DIN VDE 0295) class 5                                                                                 |
| Sheath diameter                   |   | 6 mm                                                                                                                             |
| Bending radius                    |   | > 10 x cable diameter, moving<br>> 8 x cable diameter, fixed                                                                     |
| Sheath stripping force            |   | max. 80 N / 500 mm                                                                                                               |
| Sheath color                      |   | black (similar to RAL 9005)                                                                                                      |
| Number of cores                   |   | 8                                                                                                                                |
| Core cross-section                |   | 0.25 mm <sup>2</sup>                                                                                                             |
| Cores color                       |   | Core 1: white<br>Core 2: brown<br>Core 3: green<br>Core 4: yellow<br>Core 5: grey<br>Core 6: pink<br>Core 7: blue<br>Core 8: red |
| Core construction                 |   | 14 x 0.15 mm Ø                                                                                                                   |
| Length                            | L | 0.3 m                                                                                                                            |
| Cable code                        |   | Li 9Y 11Y 8 x 0,25                                                                                                               |
| <b>Material</b>                   |   |                                                                                                                                  |
| LABS free                         |   | yes                                                                                                                              |
| Halogen-free                      |   | yes                                                                                                                              |
| Plug connector                    |   |                                                                                                                                  |
| Knurled screw connection          |   | Zinc die-casting, nickel-plated                                                                                                  |
| Body                              |   | TPU, black                                                                                                                       |
| Contact surface                   |   | Au                                                                                                                               |
| Flammability                      |   | V-2                                                                                                                              |
| Cable                             |   |                                                                                                                                  |
| Sheathing                         |   | PUR based on polyether                                                                                                           |
| Core insulation                   |   | PP                                                                                                                               |
| UV resistance                     |   | yes                                                                                                                              |
| Chemical resistance               |   | good                                                                                                                             |
| Oil resistance                    |   | yes                                                                                                                              |
| Cooling lubricant resistance      |   | yes                                                                                                                              |
| Microbial resistance              |   | yes                                                                                                                              |
| Hydrolysis resistance             |   | yes                                                                                                                              |
| Flammability                      |   | FT2                                                                                                                              |

Release date: 2020-09-17 Date of issue: 2020-09-17 Filename: 239999-100003\_eng.pdf

Connection Assignment



|   |       |       |       |    |
|---|-------|-------|-------|----|
| 1 | _____ | ..... | _____ | WH |
| 2 | _____ | ..... | _____ | BN |
| 3 | _____ | ..... | _____ | GN |
| 4 | _____ | ..... | _____ | YE |
| 5 | _____ | ..... | _____ | GY |
| 6 | _____ | ..... | _____ | PK |
| 7 | _____ | ..... | _____ | BU |
| 8 | _____ | ..... | _____ | RD |

Release date: 2020-09-17 Date of issue: 2020-09-17 Filename: 239999-100003\_eng.pdf