




## Connection cable V19-W-BK10M-PUR-U-V19-G

- Suitable for drag chains and abrasion resistant
- Suitable for robotic applications / torsion resistant
- Degree of protection IP67 / IP68 / IP69
- Free from substances that impair paint wetting
- Resistant to microbes and hydrolysis
- cURus approval
- UV resistant
- Halogen-free
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching

Cordset M12 socket angled to M12 plug straight A-coded, 8-pin, PUR cable black, UL-approved, drag chain suitable, torsion resistant



### Dimensions



### Technical Data

#### General specifications

|                    |                  |
|--------------------|------------------|
| <b>Connector 1</b> |                  |
| Connection         | socket           |
| Construction type  | M12              |
| Style              | right angle      |
| Locking            | screw connection |
| Number of pins     | 8                |
| Coding             | A-coded          |
| <b>Connector 2</b> |                  |
| Connection         | Male connector   |
| Construction type  | M12              |
| Style              | straight         |
| Locking            | screw connection |
| Number of pins     | 8                |
| Coding             | A-coded          |
| UL File Number     | E231213          |

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

**PEPPERL+FUCHS**

## Technical Data

### Electrical specifications

|                   |                |                 |
|-------------------|----------------|-----------------|
| Operating voltage | U <sub>B</sub> | max. 30 V AC/DC |
| Operating current | I <sub>B</sub> | max. 2 A        |

### Conformity

|                      |  |                                     |
|----------------------|--|-------------------------------------|
| Degree of protection |  | EN 60529                            |
| Plug connection      |  | connector M12 x 1 : IEC 61076-2-101 |
| Flammability         |  | UL 1581; DIN EN 60332-2-2           |
| Halogen-free         |  | IEC 60754-1                         |

### Approvals and certificates

|             |  |                                                    |
|-------------|--|----------------------------------------------------|
| UL approval |  | AWM STYLE 20549 AWM I/II A/B 80°C 300V FT2 (cable) |
|-------------|--|----------------------------------------------------|

### Ambient conditions

|                     |  |                                |
|---------------------|--|--------------------------------|
| Ambient temperature |  |                                |
| Plug connector      |  | -40 ... 90 °C (-40 ... 194 °F) |
| Cable, fixed        |  | -40 ... 80 °C (-40 ... 176 °F) |
| Cable, flexing      |  | -20 ... 80 °C (-4 ... 176 °F)  |
| Pollution degree    |  | 3                              |

### Mechanical specifications

|                        |   |                                                                                                                                  |
|------------------------|---|----------------------------------------------------------------------------------------------------------------------------------|
| Plug connector         |   |                                                                                                                                  |
| Tightening torque      |   | 0.6 Nm                                                                                                                           |
| Loosening protection   |   | available                                                                                                                        |
| Tool installation      |   | straight knurling                                                                                                                |
| Mating cycles          |   | min. 100                                                                                                                         |
| Degree of protection   |   | IP67 / IP68 / IP69                                                                                                               |
| Cable                  |   | according to IEC/EN 60228 (DIN VDE 0295) class 5                                                                                 |
| Sheath diameter        |   | 6 mm                                                                                                                             |
| Bending radius         |   | > 10 x cable diameter, moving<br>> 8 x cable diameter, fixed                                                                     |
| Sheath stripping force |   | max. 80 N / 500 mm                                                                                                               |
| Sheath color           |   | black (similar to RAL 9005)                                                                                                      |
| Number of cores        |   | 8                                                                                                                                |
| Core cross-section     |   | 0.25 mm <sup>2</sup>                                                                                                             |
| Cores color            |   | Core 1: white<br>Core 2: brown<br>Core 3: green<br>Core 4: yellow<br>Core 5: grey<br>Core 6: pink<br>Core 7: blue<br>Core 8: red |
| Core construction      |   | 14 x 0.15 mm Ø                                                                                                                   |
| Length                 | L | 10 m                                                                                                                             |
| Cable code             |   | Li 9Y 11Y 8 x 0,25                                                                                                               |

### Material

|                          |  |                                 |
|--------------------------|--|---------------------------------|
| LABS free                |  | yes                             |
| Halogen-free             |  | yes                             |
| Plug connector           |  |                                 |
| Knurled screw connection |  | Zinc die-casting, nickel-plated |
| Body                     |  | TPU, black                      |
| Contact surface          |  | Au                              |
| Flammability             |  | V-2                             |
| Cable                    |  |                                 |
| Sheathing                |  | PUR based on polyether          |
| Core insulation          |  | PP                              |
| UV resistance            |  | yes                             |
| Chemical resistance      |  | good                            |
| Oil resistance           |  | yes                             |

Release date: 2020-09-18 Date of issue: 2020-09-18 Filename: 240776-100030\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

|                              |     |
|------------------------------|-----|
| Cooling lubricant resistance | yes |
| Microbial resistance         | yes |
| Hydrolysis resistance        | yes |
| Flammability                 | FT2 |

Connection Assignment

