

Technical data sheet

Connection cable

Part no.: 50113468

KB JST-M12A-8P-Y-3000

Contents

- Technical data
- Electrical connection

Figure can vary

Technical data

Basic data

Suitable for	LSIS 400i standard
Suitable for interface	RS 232

Connection

Connection 1

Type of connection	Connector
Thread size	M12
Type	Male
No. of pins	8 -pin
Encoding	A-coded
Design	Axial

Connection 2

Type of connection	JST ZHR
No. of pins	10 -pin
	6 -pin

Connection 3

Type of connection	Connector
Thread size	M12
Type	Female
No. of pins	8 -pin
Encoding	A-coded
Design	Axial

Cable properties

Number of conductors	10 Piece(s)
Sheathing color	Black
Shielded	Yes
Cable design	Interconnection cable
Cable diameter (external)	8.5 mm
Cable length	3,000 mm
Sheathing material	PUR
Suitability for drag chains	No

Classification

Customs tariff number	85444290
eCl@ss 8.0	27279218
eCl@ss 9.0	27060311
ETIM 5.0	EC001855
ETIM 6.0	EC001855

Electrical connection

Connection 1

Type of connection	Connector
Thread size	M12
Type	Male
No. of pins	8 -pin
Encoding	A-coded
Design	Axial

Connection 2

Type of connection	JST ZHR
No. of pins	10 -pin
	6 -pin

Connection 3

Type of connection	Connector
Thread size	M12
Type	Female
No. of pins	8 -pin
Encoding	A-coded
Design	Axial